Tank Capacity:max loading weight 8000kg.(other chassis with bigger or smaller capacity available)

Tank Material:Inner side:4mm 304-2B food-grade stainless steel

Middle:60-100mm Polyurethane foam insulation

Outer side:1.2mm 201 stainless steel

Feartures:1.CIP auto-cleaning with 360°cleaning angles

- 2.Use food-grade polished stainless steel for parts that touch with milk
- 3. Optimized tank design to minimize milk remaining.
- 4.Thick polyure thane foam insulation to ensure 24h temperature change ${<}1^{\circ}{\rm C}$

Below photo includes our different milk tank trucks. We supply from 2cbm mini tank to 20cbm heavy duty type, even larger semi-trailer tanks. Please contact us(mobile/whatsapp +86 186 0722 2773) to learn more details before placing order.

| | Overall dimension(L*W*H mm) | 5990*1960*2380 |
|----------|-----------------------------|--|
| | Gross Vehicle Mass(kg) | Approx7300 |
| | Curb weight(kg) | Approx3150 |
| | Rated load(kg) | Approx4020 |
| | Combustion/Fuel Type | Diesel |
| Chassis | Drive type/traction system | 4*2 |
| | Wheel base (mm) | 3300 |
| | Tyre type | 6+1 7.00R16 |
| | Transmission | 5 forwarder,1 reverse gear, manual operation |
| E Engine | Model | 4KH1CN5LS |
| | Engine Type | Vertical array, water-cooled, four- stroke, inter-cooling |
| | Maximum Horse Power(hp) | 120 /88kw |
| | Displacement(L) | 2999L |
| | Emission | EuroV |
| | maximum torque | 220 N/m |

| Tanker body | Tank dimension | 3400/1600/1200 |
|-------------|----------------------------|-----------------|
| | water tank volume | 5000 Liters |
| | the material of tanker | stainless steel |
| | the thickness of tank body | 4.5 mm |

Reference Pictures





















