| Main specification | | | | | | | | | |
|--------------------------------|----------------------------|--|----------------------|-----------------------|------------------------------------|-------------------------|----------------|---------------------|--|
| Product model and na | QL10703HARY water truck | | | | | | | | |
| Gross weight(Kg) | | 7300 | | Drive type | | 4X | 4X2 | | |
| Payload(Kg) | | 4200 | | Overall dimension(mm) | | | 5990x1900x2250 | | |
| Curb weight(Kg) | | 2970 | | Cab seats | | ts 2 | | | |
| Approach/departure angle(°) | | 24/16 | | Front/rear hang(mm | | nm) 10 |) 1015/1615 | | |
| Axle No. | | 2 | | Wheelbase(mm) | | | 3360 | | |
| Axle load(Kg) | | 2580/4720 | | Max speed(Km/h) | | 95 | 95 | | |
| Chassis specification | n | • | | • | | • | | | |
| Chassis model | QL1 | QL10703HARY M | | Manufacturer | | Qingling Motor Co., Ltd | | | |
| Brand name | ISUZU | | Dimension(m) | | mm) | 5900x1880 | | 2220 | |
| Tyre specification | 7.00-16 | | Tyre No. | | 6 | | | | |
| Steel spring number | 8/6+5 | | Front track base(mm) | | 1504 | | | | |
| Fuel type | Die | Diesel | | Rear track base(mm) | | 1425 | | | |
| Emission standard | Euro 4 | | Transmission | | 5 forward gear,1 reverse gear(MSB) | | | | |
| Cab | Sin | ngle row, Air condition and power steering | | | | | th US | BB interface radio. | |
| Engine model | Eng | jine manufac | turer | | Displacement(ml) | | Por | wer(Kw) | |
| 4JB1CN | 1 - | Qingling ISUZU Engine Co.,Ltd | | | 2771 | | 72 | | |
| Performance | | | | | | | | | |
| Tank volume[m³[| 3 to 5(3000 to 5000liters) | | | Tank material | | al | Ca | arbon steel Q235 | |
| Water pump model | 6 | 65QZ40/45 | | | Water pump flow(n | | |) | |
| Watering width(M) | ≥14 | | | | Water cannon range (M) | | ≥: | 28 | |
| Feature and Applica | tion | | | | | | | | |

- 1). Equipped with high power self-suction water pump that characterized by high-pressure and fast speed suction.
- 2). Equipped with front, rear and side sprinklers and high position sprinkler, and rear working
- 3). The water cannon which is installed on the working platform can rotate by 360 degree and the water flow can be adjusted into various rain shape. There are straight shape, heavy rain, moderate rain and drizzle etc. The max range can reach 30M.
- 4). Equipped with fire coupling, flow valves, filter screen and water level gauge.
- 5). According to customers' request, the crane, high working platform and spraying machine also can be equipped.
- 6). Mainly used for washing on urban roads, watering and greening on trees, green belts and lawn and dust full of construction sites. And also used for drinking water delivery and fire fighting function etc.

Japan ISUZU mini 5000liter water truck

Image









