Product model name			Compression Garbage Truck						
Gross weight(Kg)			7300			Driving type	4*2		
Payload (Kg)			2100,1750			Overall dimension (mm)	6460,6600,6710,6860 X1990X2650		
Curb weight(Kg)			5070,5420			Cab seats (man)	2		
Approach/departure angle (°)			24/12			Front/rear hang(mm)	1015/2085		
Axle No.			2			Wheelbase (mm)	3360		
Axle load(Kg) Chassis specifications			2580/4720			Max speed(Km/h)	110		
	QL1070A5HAY			Manufacture			Qingling automobile co. LTD		
ISUZU 60	ISUZU 600P				Overall dimension (mm)				
7.00R16	7.00R16 14PR			Tires No.			6+1		
					rack(mm)		1504		
DIESEL	DIESEL				ack(mm)		1425		
EUROP V	EUROP V				ox		5 forward gears		
With Air o	With Air conditioning and power steering.								
Engine m	Engine manufacture				Displacement(ml)		Power(Kw)		
Qingling i	Qingling isuzu (chongqing) engine co. LTD				2999		96		
Body capacity [m [] 5-6			Hopper capacity[]m []				0.8		
						36			
Control system Electric control a Main Characteristic				and manual hydraulic control					
	ISUZU 60 7.00R16 DIESEL EUROP V With Air c Engine m Qingling i	7300 2100; 2100; 2100; 24/12 2 2 2580/- QL1070A5HAY ISUZU 600P 7.00R16 14PR DIESEL EUROP V With Air conditioning and powe Engine manufacture Qingling isuzu (chongqing) engi	7300 2100,1750 2100,1750 5070,5420 24/12 2	7300 2100,1750 2100,1750 2100,1750 2100,1750 200,5420 24/12 2 2 2580/4720 2580/4720 2 2580/4720 2 2 2580/4720 2 2 2 2 2 2 2 2 2	7300 2100,1750 2100,1750 2100,1750 240,1750 24/12 24/12 2 2580/4720 2880/4720 2880/4720 2880/4720 2880/4720 38	7300 2100,1750 2100,1750 2100,1750 200,075,420 24/12 2 2 2580/4720 2580/4720	7300 Driving type		

- Main Characteristic
 1] Can choose 240Ljsingle bin double bins or 360Lj 660L 1100L standard bin lifting and turnover mechanism can also choose ground hopper and other kinds of loading mechanism.
 2] With manual and automatic two sets of control method, the operator can control in the cabin, in the middle side or the back of the truck, very convenient and efficient.
 3] With working device of emergency braking stop button or a control in the cabin, in the middle side or the back of the truck, very convenient and efficient.
 3] Garbage body use frame design, elegant, strong structure, large effective capacity.
 5] Equipped with special collection box, sewage directly into the sewage tank in the process of compression, that is effectively prevent second pollution caused by sewage leaks.
 6] Through hydraulic system design, the truck achieve the function of two-way garbage compression, that is improve the compressibility, make the compression ratio up to 1:2.5, the garbage can reach more then 600[800kg]m3 after compression.

Reference pictures

















