Main specificatio	n								
Product model and	)	QL1070A1KAY Wrecker truck							
Gross weight(Kg)		7300		Drive type			4X2		
Curb weight(Kg)		4370		Overall dimension(mm)			7300X2300X2460		
Approach/departure angle(°)		24/14		Cab seats			2		
Axle No.		2 F		Front/rear hang(mm)			1015/2470		
Axle load(Kg)		2580/4720 V		Wheelbase(mm)			3815		
Max speed(Km/h)		105							
Chassis specifica	tion		•						
Chassis model	QL1070A1		1KAY Manu		ufacturer		Qingling Motor Co.,Ltd		
Brand name	ISUZU		Dime		ension(mm)		6645X1880X2160		
Tyre specification	7.00-16 14P		4PR Tyre No.		No.	6 an		nd 1 for the spare	
Steel spring number	8/6+5			Front trac		k base(mm)	1504	1504	
Fuel type	Diesel		Rear		track base(mm)		1425		
Emission standard	Euro 4		Trans		smission		MSB,5 forward gear,1 reverse gear		
Cab	Single row, luxurious interior trim with seats and power steering with air condition.								
Engine model	Engir	ne m	anufacturer		Displacement		t(ml)	ml) Power(Kw)	
4KH1-TCG40	Qing	ling	ISUZU Eng	ngine Co.,Ltd		2999		88	
Performance	•								
Flat length(mm) 560		560	0		Flat width(mm)				2300
Max flatbed carrying 400 veight(Kg)		400	0		Max lift weight(Kg)		(g)		3000
Vehicle accessor	ies				-				
Training wheels, St	eel wi	re ro	pe, Banda	ige, Ala	arm l	amp, Tyre co	vers,	Jack,	Spare tyre, Drivers' tools
Wrecker Truck In	struc	tion							
It has the powerful	functi	on a	nd can ca	rry two	cars	at the same	time.	It is	railer and road rescue truck. the ideal choice for road ad repair and rescue.

## Japanese ISUZU tow truck Image











