

# Spec. Japanese ISUZU Tow Truck

Main specification			
Product model and name	JDF5071TQZQ4 Wrecker truck		
Gross weight(Kg)	6900	Drive type	4X2
Curb weight(Kg)	5505	Overall dimension(mm)	7400X2300X2410,2600
Approach/departure angle(°)	21/10	Cab seats	3
Axle No.	2	Front/rear hang(mm)	1110/2475
Axle load(Kg)	2350/4550	Wheelbase(mm)	3815
Max speed(Km/h)	95		
Chassis specification			
Chassis model	QL10909KARY	Manufacturer	Qingling Motor Co., Ltd
Brand name	ISUZU	Dimension(mm)	6980x2170x2350
Tyre specification	8.25-16-14PR	Tyre No.	6 and 1(for the spare)
Steel spring number	8/10+6	Front track base(mm)	1680
Fuel type	Diesel	Rear track base(mm)	1650
Emission standard	Euro 4	Transmission	6 forward gear, 1reverse gear(ISUZU MLD)
Cab	Cab color: white red or other colors as your request. Single row, Luxurious interior trim with seats,Power steering with air condition.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
4HK1-TCG40	Qingling ISUZU Engine Co.,Ltd	5193	139(190HP)
Performance			
Flat length(mm)	5600	Flat width(mm)	2300
Max flat carrying weight(Ton)	5	Max lift weight(Ton)	3
Vehicle accessories			
Training wheels, Steel wire rope,bandage, Alarm lamp, Tyre Covers,Jack, spare tyre ,drivers' tools			

## Japanese ISUZU Tow Truck Image



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clcwtruck.com](mailto:brenda@clcwtruck.com)













basic equipment

warning light



hydraulic winch



tow wheeler



operating valves



real towing device



washing hand tank



New type flat bed .  
has big friction  
force will make  
truck more safety .  
and the flatbed  
more lighter

Tilte angle flatbed truck



full sit ground flatbed truck

