⊔Main speciπcations⊔								
Product model name CLQ5060JSQ4JX Truck With Crane								
Gross vehicle weight(kg)	5835	7 1			4 x 2			
Payload(kg)	2000	cab seats (man)				2+3		
Curb weight(Kg)	3510	Overall dimension (m			nm)	m) 5995×2000×2850		
Approach/departure angle (°)	27/12	Box internal dimension(mm)				2750	×1770×400	
Number of axles	2	Front/rear hang(mm))	1015/1620		
Axle load(Kg)	1940/3895	Wheelbase(mm)			3360			
Max speed(Km/h)	90							
<pre>Chassis specifications</pre>	•	-						
Chassis model	JX1060TSG24	В	Brand name			JMC		
Manufacturer	Jiangling Motors Corporation, Ltd	Т	Tires No.			6		
Approach/departure angle (°)	27/18.5	7/18.5 Tire specification				7.00R16LT		
Steel spring number	7/5+5	F	Front track(mm)		1385			
Fuel type	Diesel		Rear track(mm)		1425			
Emission standard	Euro VI	T	Transmission			5 gears		
Cabin	Double cab, luxurious interior trim and seat, with power steering, air conditioning.							
Engine model	Engine manufacturer	ine manufacturer Displace				ကl)	Power(Kw)	
JX493ZLQ4	Jiangling Motors Corp	poration, Ltd 2771					80	
□Crane specification								
Crane model	SQS22	Crar	Crane brand		XCMG			
Type of Crane	Telescopic boom	Crane weight (kg)			1000			
Max lifting weight∏kg∏	2000	Max lift height[]m[]			6.8 / 9			
Working radius(m)	5.8 / 7.7	Ope	ration met	Side control				
Number of arms	2/3	Outi	rigger (pcs	2 or 4				
<pre>□Functions□</pre>								

□Main specifications□

The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.













Kindly note we can provide straight boom crane and folding crane according to customers' requirement. And the crane also can be equiped on flatbed truck for transport construction machinery like excavator, wheel loader, harvest ect undisassemble machines.

















