DFAC Duolika 3800 Road Sweeper Truck

Main specifications			
Product HCQ5081TSLDFA Road Sweeper Truck			
model∏name			
Gross weight(Kg)	8275	Drive type	4 X 2
Payload (Kg)	2100	Overall dimension	7160×2200×2750
		(mm)	
Curb weight(Kg)	5980	cab seats (man)	3
Approach /	24/12	Front/rear hang(mm)	1210/2150
departure			
angle(°)			
Number of axles	2	Wheelbase(mm)	3800
Axle load	3310/4965	Max speed(Km/h)	95
Chassis specifications			
Chassis model	EQ1070TJ9AD3	Manufacturer	DongFeng Motors Co., Ltd.
Brand name	DongFeng	Overall	6815×2080×2440
		dimension(mm)	
Tire specification	7.50R16	Tires No.	6
Steel spring	8/10+7,11/9+7	Front track(mm)	1770
number			
Fuel type	Diesel	Rear track(mm)	1586
Emission	Euro IV	Transmission	5 forward gear,1
standard			reverse gear
Cabin	Car interiors, with the direction of power and USB interface, cassette		
	player, with air conditioning,		
Engine model	Engine manufacture	Displacement(ml)	Power(Kw)
CY4102-E3C	Dongfeng Chaoyang Chaochai Power Co.,Ltd	3856	88(120HP)
YC4FA120-33	Guangxi Yuchai	2982	88(120HP)
	Machinery Co.,Ltd		
Road Sweeper Pe			
Trash tank volume (m³)	5	Water tank volume (m³)	2
Material of trash tank	Stainless steel	Material of water tank	Stainless steel
Model of	JX493G	Power of auxiliary	57KW
auxiliary engine		engine(Kw)	
Manufacturers of	JiangXi ISUZU Engine	Max sweeping	3200
auxiliary engine	Co., Ltd.	width(mm)	
Sweeping speed	3-20	Sweeping capacity	9000- 60000
(km / h)		□□/h□	
Maximum Grain	100mm\±1.5kg	Cleaning Rate	96%
size and quality			
(mm)			
Road Sweeper Features			

- 1. The control box is in the cab, all kinds of system electrical centralized to control, and easy to operate!
- 2, Four scan disk combinated with suction nozzle in working. according to a different cleaning conditions Scan disk speed can be controlled by choosing three gear-High, medium and low, which can make sure there be have a good cleaning results in a variety of pollution status. and when met the obstacle, the scan disk can be have a automatic avoidance protections and features automatic reset function, and retracted automaticly, then reseted automaticly after over some obstacles!
- 3.Both of side of the scan disk can be working altogether, or unilateral work independently.















