

Wuling refrigerated truck adopts the SAIC 1.5L displacement gasoline engine, 108 horsepower, and the national five emission standard. The engine model is SAIC-GM-Wuling: L3C, 5-speed gearbox, 175/75R14C vacuum tire.

The overall dimensions of the vehicle are (mm) : 4575*1615*2370 The internal dimensions of the car are (mm) : 2450*1400*1400=4.8 cubic. The rated mass is : 360Kg, the curb weight is : 1480Kg , the total mass is : 1970Kg
Wuling Refrigeration The car's insulated car body is made of inner and outer glass-reinforced plastic polyurethane, vacuum composite press, the bottom plate is aluminum tread plate, the door frame locks are made of stainless steel, and the car interior has a ceiling light. The car insulation materials are thermal insulation, fire retardant insulation materials, domestic refrigeration units, the lowest temperature can reach -15 degrees, and the optional side door structure car.

Third, the optional cold: can root according to customer demand for cars to choose different units,customer-selectable -5 °C, -10 °C, -15 °C , -18 to -20 °C refrigeration units , refrigeration units brands aremade in China Jin Up to K brand, Hana, Hanxue, Huatai, Song Han, Kaixue, super cool .. and other refrigeration units, imported refrigeration unit brands are: the United States Carrier, the United States Cold King . Refrigeration units divided into separate units and split type group ! This model can be equipped with "cooling + heating" dual-temperature unit (control temperature range of +20 ° C to -18 ° C) can be used in the northeast region and Inner Mongolia Xinjiang and other cold regions!

Fourth, the optional configuration: rail meat hook, T-slot ventilation, the right side door open, real-time monitoring the temperature of the tape printing device, mounted inside the envelope fabric must seafood optionalstainless steel, may beoptional external power supply 12V-24V (vehicle When stopped, thecar is cooled by an external power supply).

V. Vaccine Drug loading: do GSP drug product must be installed authentication envelope around, and a bottom surface of the envelope 5 through the duct,and atemperature and humidity recorder tape printing apparatus!

Sixth, the medical waste: the inside of the body must be made of fully enclosed stainless steel, with stainless steel closed inner door, installed anti-virus spray device, installed ultraviolet anti-virus device, install waste liquid spill box device!

Wuling refrigerated truck main technical parameters			
product name	DA5029XLCPYA refrigerated truck	Emission Standards	Country five
Dimensions (mm)	4530×1600×2365	Environmental protection standards:	Yes
Car size (mm)	2440×1375×1410	license	Blue card
Total mass (kg)	1970	Fuel	gasoline
Rated mass (kg)	360	Number of tires:	4
Curing quality (kg)	1480	Top speed (km/h)	120
Tire specifications	175/75R14C, 165R14LT, 175/75R14LT		

Wuling refrigerated truck engine parameters

engine model	Engine manufacturer	Displacement (ML)	Power (ML)
L3C	SAIC-GM-Wuling Automobile Co., Ltd.	1485	79

SGMW refrigerator truck

Image as below:



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com







Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@ciclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com

