Main specification									
Product model and name		ZZ1087D3814D183 HOWO Wrecker truck							
Gross weight(Kg)		8280 Dri		ive type			4X2		
Curb weight(Kg)		35 Overall		l dimension(mm)			7430X2300X2500		
Approach/departure angle(°)		/11	Cab sea	ats	3			3	
Axle No.			Front/rear hang(mm)			1160/2470			
Axle load(Kg)		70/5410	5410 Wheelbase(mm)			3	3800		
Max speed(Km/h)			Steering type					eft hand drive or right hand rive can be offered	
Chassis specification									
Chassis model	ZZ1087E	Ma	Manufacturer			China SINOTRUK Group Jinan Commercial Vehicle Co.,Ltd			
Brand name	SINOTRI	Dimension(mm)			6810x2010x2350				
Tyre specification	7.50R16	Tyr	Tyre No.			6			
Steel spring number	3/5+3	Fro	Front track base(mm)			1600			
Fuel type	Diesel	Rea	Rear track base(mm)			1535			
Emission standard	Euro 3	Tra	Transmission			5 forwarder gear,1 reverse gear(manual)			
Cab	Any color as your request. single row, luxurious interior trim with seats.Cab can be tippable forwardly. And power steering with optional air condition.								
Engine model	Engine n	Engine manufacturer			Displacement(ml)		Power(Kw)		
CY4102-E3C (with turbo)		Dongfeng Chaoyang Chao Power Co.,Ltd			3856		91(125HP)		
Performance									
Flat length(mm)		5600	5600		Flat width(mm)			2300	
Max flatbed carrying capacity(Kg)		4000	4000		Max lift weight(Kg)			00	
Hydraulic parts		Imported	Imported						
Vahicla accessories		•					•		

#### Vehicle accessories

Training wheels, Steel wire rope, Bandage, Alarm lamp, Tyre covers, Jack, Spare tyre, Drivers' tools

#### **Wrecker Truck Instruction**

The full name of wrecker truck is named road wrecker truck, also called trailer and road rescue truck. It has the powerful function and can carry two cars at the same time. It is the ideal choice for road management department and automobile repair plat to proceed to the road repair and rescue.


















# **BATCH DELIVERY**



















# **BRACKET ARM**

Can be completed at one one-time two failure car cleaning, high efficiency



Can implement a drag two function, bracket part can also realize the fault car consignment





## OPERATION LEVER







The action of each part is controlled by the handle of the reversing valve

03

## **LIFT HYDRAULIC CYLINDER**

lifting hydraulic cylinder make the flatbed moves down until the back side touches the ground



The auxiliary frame is raised to a certain tilt angle by the hydraulic cylinder of lifting mechanism during work.



04

### **BIGGER LOADING CAPACITY**

Flatbed is made from Q235 steel press forming with high strength





#### FLATBED WRECKER TRUCK MOUNTED CRANE

Optional installations are availabe for your actual demand

