

Technical Specification

Main specification				
Product model and name		JDF5190GXFAP70Z-A Foam Fire Truck		
Gross weight(Kg)	19000	Drive type	4x2	
Payload(Kg)	6500	Overall dimension(mm)	8950×2500×3510	
Curb weight(Kg)	12050	Cab seats	2+4	
Approach/departure angle(°)	16/10	Front/rear hang(mm)	1500/2650	
Axle No.	2	Wheelbase(mm)	4600	
Axle load(Kg)	6000/13000	Max speed(Km/h)	90	
Chassis specification				
Chassis model	ZZ1167M4617C	Manufacturer	China SINOTRUK Group Co.,Ltd	
Brand name	SINOTRUK(HOWO)	Tyre No.	6	
Tyre specification	11.00-20 18PR	Front track base(mm)	2022,2041	
Steel spring number	10/9+6	Rear track base(mm)	1830	
Fuel type	Diesel	Transmission	10 forward gear, 2 reverse gear	
Emission standard	Euro 3			
Cab	Four opening doors and whole flat top with crew cab, and all steel frame welded structure.Air condition is optional.			
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)	Horsepower(HP)
WD615.92E	China Heavy duty Auto Group Co.,Ltd	9726	196	267
Foam and powder fire truck performance				
Water tank volume(L)	4000-5000L	Foam tank volume(L)	1000L-2000L	
Fire monitor	Model:PL32. water and foam tank dual purpose fire monitor. Foam range:≥50m/1.0MPa Water range:≥55m/1.0MPa			
Fire pump	Model: CB10/40. Flow rate:40L/S. Pressure: 1.0MPa. Water pump drive type: sandwich type power take-off			
Feature				
Water and powder tank combination fire truck can spray water and powder at the same time.Adopted the independent passengers room and has 6 seats.Both dry powder and valves are made by stainless steel.This truck can be used to put out all kinds of fire,especially applied to save the liquid and gas fire etc.It is the indispensable fire extinguishing equipment for the fire department.				

SINOTRUK HOWO 6000Liter foam fire truck

Foam Fire Truck Image





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@cclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com