

Main specifications			
Product model name	CDW5040JSQA3Q4 Truck With Crane		
Gross vehicle weight(kg)	4495	Drive type	4 x 2
Payload(kg)	1450	cab seats (man)	3
Curb weight(Kg)	2850	Overall dimension (mm)	5995×2250×3200
Approach/departure angle (°)	24/14	Box internal dimension(mm)	3450×2150×600
Number of axles	2	Front/rear hang(mm)	1285/1350
Axle load(Kg)	1705/2790	Wheelbase(mm)	3360
Max speed(Km/h)	80		
Chassis specifications			
Chassis model	CDW1040HA3Q4	Brand name	Sinotruk
Manufacturer	China Heavy Duty Truck Group Co., Ltd. Chengdu ace commercial vehicles	Tires No.	6
Approach/departure angle (°)	24/23	Tire specification	8.25-16
Steel spring number	11/11+9	Front track(mm)	1670
Fuel type	Diesel	Rear track(mm)	1590
Emission standard	Euro IV	Transmission	5 gears
Cabin	1880 Single cab, tiltable luxurious interior trim, seat. with power steering, air conditioning can be equiped if customer requires.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
YN38CRD1	Kunming Cloud Power Co., Ltd	3760	95
Crane specification			
Crane model	SQS22	Crane brand	XCMG
Type of Crane	Telescopic boom crane	Crane weight(kgs)	485
Max lifting weight kg	2000	Max lift height m	6.8 / 9
Working radius(m)	5.8 / 7.7	Operation method	Side control
Number of arms	2 / 3	Outrigger (pcs)	2 / 4
Functions			
The truck consists of chassis, box, power take-off and crane, achieving cargo lifting and moving through hydraulic lifting and telescopic system. In general, H-type outrigger is equipped to realize its stability. To be further strengthened stability of the truck, rear outrigger also can be equipped if the customer require. The truck can 360 ° continuously rotate.			

Sinotruk Truck Mounted Crane China Supplier, 2000 Kgs Truck Crane Manufacturer in China, Lorry Crane Supplier

Product Image







