

SPECIFICATION		
Truck Model		SX3255DR404
Truck Brand		Shacman H3000
Driving type		Left Hand drive or Right hand drive
Dimension(LxW xH)(unloaded)(mm)		8750x2500x3750
Cargo body size (L*W*H)		5800x2300x1500
Cargo body thickness(mm)		bottom:8mm, side:6mm
Lift type of Carriage		Ventral lifting
Approaching angle/Departure angle(°)		19/23
Overhang(front/rear) (mm)		1500/1870
Wheel base (mm)		3825+1350
Max speed(km/h)		75
Curb weight(kg)		12600
Loading Weight(kg)		25000
Fuel tanker capacity(L)		300L with locking fuel cap
Clutch		Single-plate dry clutch Φ430mm
Engine Model (Made in China)	Model	WP10.380E22, 4- stroke direct injection diesel engine, 6 cylinders in line with water cooling , turbo-charging and inter-cooling
	HorsePower,max(kw/rpm)	380HP
	Emission	EURO II
	Fuel Type	Diesel
Transmission	Model	12JSD180+QH50
Brake system	Service brake	Dual circuit compressed air brake
	Parking brake	spring energy, compressed air operating on rear wheels
	Auxiliary brake	Engine exhaust brake
Steering system	Model	ZF8118 hydraulic steering with power assistance Ratio:22.2-26.2
Front axle	HF9 , Steering with double T-cross section beam Loading capacity:9000KG	

Rear axle	HC16, Pressed axle housing, central double reduction with differential locks between axles and wheels	
	Loading capacity: 16000kg	
Color	Optional	
Tire	12.00R20 Steel tires, 10+1 spare	
Electrical system	Operating voltage	24V,negative grounded
	Starter	24V,7.35KW
	Alternator	28V,1500W
	Batteries	2*12V.165Ah
	Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light.	
Cab	Shacman cab, (single sleeper, with air-condition), all-steel forward control,70°hydraulically tiltable to the front, 2- arm windscreen wiper system with 3 speeds, laminated windscreen with <u>casted-in</u> radio aerial, hydraulically damped adjustable driver's seat and rigid adjustable co-driver's seat, with heating and ventilating system, outer sun visor, adjustable roof flap, with stereo radio/cassette recorder, safety belts and adjustable steering wheel, air horn, with 4-point support fully floating suspension and shock absorbers	

Reference pictures□







