

## DongFeng [road sweeper truck](#) china supplier

### Main specifications

Product model□name	HCQ5160TXSBX5 Road Sweeper Vehicles		
Gross weight(Kg)	16000	Drive type	4 × 2
Payload (Kg)	4500	Overall dimension (mm)	8650 x 2500 x 3000
Curb weight(Kg)	11305	cab seats (man)	3
Approach / departure angle(°)	20/13	Front/rear hang(mm)	1430/2220
Number of axles	2	Wheelbase(mm)	4700
Axle load	6000/10000	Max speed(Km/h)	90

### Chassis specifications

Chassis model	DFL1160BX5	Manufacturer	DFAC
Brand name	DongFeng	Overall dimension(mm)	8290×2370×2760
Tire specification	9.00-20	Tires No.	6
Steel spring number	8/10+8,7/9+6	Front track(mm)	1880
Fuel type	Diesel	Rear track(mm)	1860
Emission standard	Euro IV	Transmission	6 forward gear
Cabin	Luxury interior and Instrument bar, with air conditioning and sleeper.		

Main engine model	Engine manufacture	Displacement(ml)	Power(Kw)
ISB180 40	Dongfeng Cummins Engine Co., Ltd.	5900	132

### Road Sweeper Performance

Trash tank volume (m³)	7	Water tank volume (m³)	3.5
Material of trash tank	Stainless steel	Material of water tank	Stainless steel
Model of auxiliary engine	EQB140-20	Power of auxiliary engine(Kw)	103KW
Manufacturers of auxiliary engine	Dongfeng Cummins Engine Co., Ltd.	Max sweeping width(mm)	3200
Sweeping speed (km / h)	3-20	Sweeping capacity □□/h□	9000- 60000
Maximum Grain size and quality (mm)	100mm\±1.5kg	Cleaning Rate	96%

### Road Sweeper Features

- 1.The control box is in the cab, all kinds of system electrical centralized to control, and easy to operate!
- 2, Four scan disk combined with suction nozzle in working. according to a different cleaning conditions Scan disk speed can be controlled by choosing three gear-High, medium and low, which can make sure there be have a good cleaning results in a variety of pollution status. and when met the obstacle, the scan disk can be have a automatic avoidance protections and features automatic reset function, and retracted automatically, then reseted automatically after over some obstacles!
- 3.Both of side of the scan disk can be working altogether, or unilateral work independently.
- 4.The core components of hydraulic systems adopts the original import!

Image as below:



Whatsapp & Telephone: +86-18607222773 Email: [brenda@cllwtruck.com](mailto:brenda@cllwtruck.com)



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clcwtruck.com](mailto:brenda@clcwtruck.com)









Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)