Since Sinc	Main specifications				
ayload(Kg) 4800 Overall dimension(mm) 8985×2500×3320 Diverbour weight(Kg) 11070 Cab seats(man) 3 Disproach/departure ingle(°) 16/9 Front/rear hang(mm) 1500/2885 Disproach/departure ingle(°) 16/9 Front/rear hang(mm) 4600 Disproach/departure ingle(°) 16/9 Front/rear hang(mm) 4600 Disproach/departure ingle(°) 1500/2885 Di	Product model,name				
Cab seats(man) 3 1500/2885 16/9 Front/rear hang(mm) 1500/2885 15	Gross weight(Kg)	16000	Drive type	4 X 2	
pproach/departure ngle(°) lumber of axles 2 Wheelbase(mm) 4600 xkle load(Kg) 6000/10000 Max speed(Km/h) 90 chassis specifications chassis model ZZ1167M4617C Manufacture Sinotruk group jinan truck co., LTD trand name HOWO Overall dimension(mm) 7990×2496×2958 fire specification 11.00-20 Tires No. 6 teel spring number 10/9+6 Front track(mm) 2022,2041 uel type Diesel Rear track(mm) 1830 mission standard Euro III Transmission 6 forward gear,1 reverse gear cabin Luxury interior and Instrument bar, with air conditioning and sleeper. fingine model Engine manufacture Displacement(ml) Power(kw) VD615.92 China national heavy duty truck group co., LTD the whole machine performance parameters ank volume[m³] 10 The volume of asphalt spreader(L/m²) 0.2[]3.5 praying error ±1.5% The number of nozzles and control leating method Italy imports of diesel burner heating (200,000 kcal / h) pray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Payload(Kg)	4800	Overall dimension(mm)	8985×2500×3320	
Ingle(°) 10/9 Front/real hang(min) 1500/2865 Itumber of axles 2 Wheelbase(mm) 4600 Ixide load(Kg) 6000/10000 Max speed(Km/h) 90 Ixide load(Kg) 6000/10000 Max speed(Km/h) 90 Ixide load(Kg) 6000/10000 Max speed(Km/h) 90 Ixide load(Kg) 6000/10000 Max speed(Km/h) 7990×2496×2958 Ixide specification 11.00-20 Tires No. 6 Ixide spring number 10/9+6 Front track(mm) 2022,2041 Ixide lype Diesel Rear track(mm) 1830 Ixide lype Diesel Rear track(mm) 6 forward gear,1 reverse gear Ixide labin Luxury interior and Instrument bar, with air conditioning and sleeper. Ixide labin Luxury interior and Instrument bar, with air conditioning and sleeper. Ixide labin Luxury interior and Instrument bar, with air conditioning and sleeper. Ixide labin Power(kw) Ixide labin Pow	Curb weight(Kg)	11070	Cab seats(man)	3	
Sinotruk group jinan truck co., LTD	Approach/departure angle(°)	16/9	Front/rear hang(mm)	1500/2885	
Chassis specifications Chassis model ZZ1167M4617C Manufacture Sinotruk group jinan truck co., LTD Grand name HOWO Overall dimension(mm) 7990×2496×2958 Grie specification 11.00-20 Tires No. 6 Acteel spring number 10/9+6 Front track(mm) 2022,2041 Luel type Diesel Rear track(mm) 1830 Grission standard Euro III Transmission Ge forward gear,1 reverse gear Cablin Luxury interior and Instrument bar, with air conditioning and sleeper. Gringine model Engine manufacture Displacement(ml) Power(kw) VD615.92 China national heavy duty truck group co., LTD The whole machine performance parameters Grank volume[m³] 10 The volume of asphalt spreader(L/m²) Spraying width(mm) 6000mm Working speed(Km/h) The number of nozzles and control Working speed(Km/h) The number of nozzles and control Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Number of axles	2	Wheelbase(mm)	4600	
Chassis model ZZ1167M4617C Manufacture Sinotruk group jinan truck co., LTD Grand name HOWO Overall dimension(mm) 7990×2496×2958 Gree specification 11.00-20 Tires No. 6 Greel spring number 10/9+6 Front track(mm) 2022,2041 Greel spring number Diesel Rear track(mm) 1830 Grission standard Euro III Transmission 6 forward gear,1 reverse gear Grabin Luxury interior and Instrument bar, with air conditioning and sleeper. Graphing model Engine manufacture Displacement(ml) Power(kw) WD615.92 China national heavy duty truck group co., LTD Graphing width(mm) G000mm Working speed(Km/h) 1.5-7 Graying width(mm) G000mm Working speed(Km/h) 1.5-7 Graying error ±1.5% The number of nozzles and control taly imports of diesel burner heating (200,000 kcal / h) Gray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Axle load(Kg)	6000/10000	Max speed(Km/h)	90	
Arand name HOWO Overall dimension(mm) 7990×2496×2958 Fire specification 11.00-20 Tires No. 6 Steel spring number 10/9+6 Front track(mm) 1830 Front track(mm) 1830 Front track(mm) Indicated spring number Indi	Chassis specifications				
Tire specification 11.00-20 Tires No. 6 Integel spring number 10/9+6 Front track(mm) 2022,2041 Italy pe Diesel Rear track(mm) 1830 Italy pe Diesel Rear track(mm) 6 forward gear,1 reverse gear Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Instrument bar, with air conditioning and sleeper. Italy interior and Italy interior and Instrument bar, with air conditioning	Chassis model	ZZ1167M4617C	Manufacture	Sinotruk group jinan truck co., LTD	
Steel spring number 10/9+6 Front track(mm) 2022,2041 Suel type Diesel Rear track(mm) 1830 Simission standard Euro III Transmission 6 forward gear,1 reverse gear Sabin Luxury interior and Instrument bar, with air conditioning and sleeper. Singine model Engine manufacture Displacement(ml) Power(kw) VD615.92 China national heavy duty truck group co., LTD 9726 196 Singine model The volume of asphalt spreader(L/m²) 0.2[]3.5 Singing width(mm) 6000mm Working speed(Km/h) 1.5-7 Singing error ±1.5% The number of nozzles and control 48 set[]one for one[] Singing method Italy imports of diesel burner heating (200,000 kcal / h) Singing medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Brand name	номо	Overall dimension(mm)	7990×2496×2958	
Diesel Rear track(mm) 1830	Tire specification	11.00-20	Tires No.	6	
Emission standard Euro III Transmission Cabin Luxury interior and Instrument bar, with air conditioning and sleeper. Engine model Engine manufacture Displacement(ml) Power(kw) China national heavy duty truck group co., LTD The whole machine performance parameters Tank volume m³ 10 The volume of asphalt spreader(L/m²) The volume of asphalt spreader(L/m²) The number of nozzles and control Engine model Engine manufacture Displacement(ml) Power(kw) 196 106 107 The volume of asphalt spreader(L/m²) The number of nozzles and control Eating method Italy imports of diesel burner heating (200,000 kcal / h) Engray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Steel spring number	10/9+6	Front track(mm)	2022,2041	
Luxury interior and Instrument bar, with air conditioning and sleeper.	Fuel type	Diesel	Rear track(mm)	1830	
Engine model Engine manufacture Displacement(ml) Power(kw) VD615.92 China national heavy duty truck group co., LTD The whole machine performance parameters Tank volume m³ 10 The volume of asphalt spreader(L/m²) The praying width(mm) 6000mm Working speed(Km/h) 1.5-7 The number of nozzles and control The number of nozzles and control asphalt, diluted asphalt, diluted asphalt, emulsified asphalt	Emission standard	Euro III	Transmission	6 forward gear,1 reverse gear	
China national heavy duty truck group co., LTD The whole machine performance parameters Tank volume machine performance parameters The volume of asphalt spreader(L/m²) The volume of asphalt spreader(L/m²) The volume of asphalt spreader(L/m²) The number of nozzles and control The number of nozzles and control control contro	Cabin	Luxury interior and Instrument bar, with air conditioning and sleeper.			
The whole machine performance parameters Tank volume machine performance parameters The volume of asphalt spreader(L/m²) The volume of asphalt spreader(L/m²) The volume of asphalt spreader(L/m²) The number of nozzles and control The number of nozzles and	Engine model	Engine manufacture	Displacement(ml)	Power(kw)	
The volume of asphalt spreader(L/m²) 0.2[3.5] In praying width(mm) 6000mm Working speed(Km/h) 1.5-7 In praying error ±1.5% The number of nozzles and control 48 set[one for one] Italy imports of diesel burner heating (200,000 kcal / h) In pray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	WD615.92	China national heavy duty truck group co., LTD	9726	196	
spreader(L/m²) 0.2[3.5] spraying width(mm) 6000mm Working speed(Km/h) 1.5-7 spraying error ±1.5% The number of nozzles and control 48 set[one for one] spraying method Italy imports of diesel burner heating (200,000 kcal / h) spray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	The whole machine performance parameters				
the praying error ±1.5% The number of nozzles and control 48 set one for one teating method Italy imports of diesel burner heating (200,000 kcal / h) The number of nozzles and control 48 set one for one teating (200,000 kcal / h) The number of nozzles and control 48 set one for one teating (200,000 kcal / h) The number of nozzles and control 48 set one for one teating (200,000 kcal / h) The number of nozzles and control 48 set one for one teating (200,000 kcal / h)	Tank volume∏m³∏			0.2∏3.5	
taly imports of diesel burner heating (200,000 kcal / h) theat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Spraying width(mm)	6000mm	Working speed(Km/h)	1.5-7	
pray medium Heat hot asphalt, modified asphalt, diluted asphalt, emulsified asphalt	Spraying error		control	48 set[]one for one[]	
	Heating method	Italy imports of diesel burner heating (200,000 kcal / h)			
he equipment use and simple introduction	Spray medium	· · · · · · · · · · · · · · · · · · ·			

ZZ1167M4617C type asphalt distributor is a kind of professional distributing emulsified asphalt, heat diluted asphalt, asphalt, high viscosity modified asphalt such as intelligent automation high-tech products. Used in the construction of high-grade highway asphalt pavement at the bottom of the transparent layer of oil spill cloth, waterproof layer, bonding layer. The asphalt made of the automobile chassis, asphalt tank, asphalt pump and spraying system, heat conduction oil heating system, hydraulic system, combustion system and control system, pneumatic system, operating platform. It is easy to operate, in the absorption of similar products at home and abroad on the basis of the technology, increased to ensure the construction quality and technical content and highlight the construction condition, construction environment improvement of humanized design. Its design is reasonable and reliable to ensure the asphalt distributing uniformity, computer control is stable and reliable, vehicle technical performance has reached the world advanced level. The vehicle can improve through my company all aspects of the work in worse conditions

Howo 12m3 Bitumen Distributor Truck for Sale





















