Main specifications							
Product model name		CLQ5310GYY5D fuel tanker truck					
Gross weight(Kg)		31000		Driving type		8x4	
Payload (Kg)		18735		Overall dimension (mm)		11990×2500×3300,369 0	
Curb weight(Kg)		12135		Cab seats (man)		3	
Approach/departure angle (°)		26/10		Front/rear hang(mm)		1460/3030	
Axle No.		4		Wheelbase (mm)		1950+4250+1300	
Axle load(Kg)		6500/6500/1800 0		Max speed(Km/h)		80	
Chassis specification	าร		6.		8		
Chassis model	DFL1	311A4	A STATE OF THE STA	ıfacture	Do	Dongfeng Motor Co.,Ltd	
Brand name	DongFeng		Overall dimension (mm)		11475×2500×3030,3600,36 90		
Tire specification	295/8	30R22.5	Tires No.		12+1		
Steel spring number	8/8/1	0	Front	track(mm)	194	10/1940	
Fuel type	diesel		Rear track(mm)		1860/1860		
Emission standard	Euro 3		Gear box		12 forward gears and 2 reverse gears		
Cab	D310 Flat top and double cab, gasbag shock the driver seat, single dashboard, with air conditioning						
Engine model	Engine manufacture			Displacement(ml )		ower(Kw)	
L340 33	Dongfeng Cummins Engine Co., LTD		ns	9460	2	50	
Performance							
Tank capacity (Liter)	32000						
Tank material	Q235 carbon steel。						
Transport medium	Petrol or diesel。						
Main Characteristic						5/4 You - You - 1 A 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	
A. with multiple baffle	plates	in the tank, t	he tank	k has the advantag	es o	f high intensity, stability.	

- **A,** with multiple baffle plates in the tank, the tank has the advantages of high intensity, stability, transporting safety etc.
- B, Oil pump is installed to suck or discharge oil, with high suction pressure and speed.
- **C**, according to users' needs, the tank can be designed as a single compartment or several compartments to contain different oils.
- **D**, according to users' needs, the side or the rear of the tank can be installed 1 to 3 self-flowing valves.

Imagens de referência:











