

Main specification			
Product model and name	CSC5380TQZZDZ Wrecker truck		
Gross weight(Kg)	38000	Drive type	8X4
Curb weight(Kg)	32070	Overall dimension(mm)	11260×2500×3570,3750
Approach/departure angle(°)	16/13	Cab seats	2
Axle No.	4	Front/rear hang(mm)	1500/2010
Axle load(Kg)	7000/7000/24000	Wheelbase(mm)	1800+4600+1350
Max speed(Km/h)	90		
Chassis specification			
Chassis model	ZZ1317N4667C	Manufacturer	China SINOTRUK Group Jinan Truck Co.,Ltd
Brand name	SINOTRUK	Dimension(mm)	11700×2496×3025,3563
Tyre specification	12.00-20	Tyre No.	12
Steel spring number	13/12,4/4/12,	Front track base(mm)	2022/2022,2041/2041
Fuel type	Diesel	Rear track base(mm)	1830/1830
Emission standard	Euro 3	Transmission	10 forward gear,1 reverse gear
Cab	HW76 medium cab, luxurious interior trim with seats. And air condition.		
Engine model	Engine manufacturer	Displacement(ml)	Power(Kw)
WD615.95E	China Heavy Duty Truck Group Co.,Ltd	9726	247
Performance			
Lifting system	Max lifting capacity(kg)	16000	
	Fully extended max lifting capacity(kg)	7310	
	Effective length of the bracket arm(mm)	1460 to 3099	
	Bracket arm flexible stroke(mm)	1639	
Hoisting system	Max hoisting capacity(kg)	18000	
	Farthest hoisting capacity(kg)	8000	
	Max hoisting height(mm)	6500	
Winch	QTY(piece)	2	
	Rated traction for each(kN)	100	
	Steel wire rope diameter(mm)	18	
	Steel wire rope length(m)	45	
Instruction			
The wrecker truck is equipped with lifting, pulling and hoisting etc. on the basis of special purpose chassis.It has the function of lifting, pulling, hoisting , lift platform and load transportation and others.It is mainly used for road fault vehicles,city peccancy vehicles and emergency rescue etc.The wrecker truck is widely used in highway,the traffic police, airport, wharf, auto repair industry and highway departments etc.It can be used to clean up the accident, fault, violation vehicles etc .timely and quickly.			

Imagens de referência:







Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com