

| SPECIFICATION                        |  |  |
|--------------------------------------|--|--|
| Truck Model                          | SX3255DR404  |  |
| Truck Brand                          | Shacman H3000  |  |
| Driving type                         | Left Hand drive or Right hand drive  |  |
| Dimension(LxW xH)(unloaded)(mm)      | 8750x2500x3750   |  |
| Cargo body size (L*W*H)              | 5800x2300x1500   |  |
| Cargo body thickness(mm)             | bottom:8mm, side:6mm   |  |
| Lift type of Carriage                | Ventral lifting  |  |
| Approaching angle/Departure angle(°) | 19/23  |  |
| Overhang(front/rear) (mm)            | 1500/1870  |  |
| Wheel base (mm)                      | 3825+1350  |  |
| Max speed(km/h)                      | 75   |  |
| Curb weight(kg)                      | 12600  |  |
| Loading Weight(kg)                   | 25000  |  |
| Fuel tanker capacity(L)              | 300L with locking fuel cap   |  |
| Clutch                               | Single-plate dry clutch Φ430mm   |  |
| Engine Model<br>(Made in China)      | Model  | WP10.380E22, 4- stroke direct injection diesel engine, 6 cylinders in line with water cooling , turbo-charging and inter-cooling |
|                                      | HorsePower,max(kw/rpm)   | 380HP  |
|                                      | Emission   | EURO II  |
|                                      | Fuel Type  | Diesel   |
| Transmission                         | Model  | 12JSD180+QH50  |
| Brake system                         | Service brake  | Dual circuit compressed air brake  |
|                                      | Parking brake  | spring energy, compressed air operating on rear wheels   |
|                                      | Auxiliary brake  | Engine exhaust brake   |
| Steering system                      | Model  | ZF8118 hydraulic steering with power assistance<br>Ratio:22.2-26.2   |
| Front axle                           | HF9 , Steering with double T-cross section beam<br>Loading capacity:9000KG |  |

|                   |  |                       |
|-------------------|--|-----------------------|
| Rear axle         | HC16, Pressed axle housing, central double reduction with differential locks between axles and wheels  |                       |
|                   | Loading capacity: 16000kg  |                       |
| Color             | Optional   |                       |
| Tire              | 12.00R20 Steel tires, 10+1 spare   |                       |
| Electrical system | Operating voltage  | 24V,negative grounded |
|                   | Starter  | 24V,7.35KW            |
|                   | Alternator   | 28V,1500W             |
|                   | Batteries  | 2*12V.165Ah           |
|                   | Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light.  |                       |
| Cab               | Shacman cab, (single sleeper, with air-condition), all-steel forward control,70°hydraulically tiltable to the front, 2- arm windscreen wiper system with 3 speeds, laminated windscreen with casted-in radio aerial, hydraulically damped adjustable driver's seat and rigid adjustable co-driver's seat, with heating and ventilating system, outer sun visor, adjustable roof flap, with stereo radio/cassette recorder, safety belts and adjustable steering wheel, air horn, with 4-point support fully floating suspension and shock absorbers. |                       |

Imagens de referência:







