

ISUZU 600P P4-P10 LED 1000000000000 SMD

LED			
		CSC5040XXCW-ISUZU	
(mm)	4495		4 x 2
(mm)	4200	(mm)	5995 × 1950 × 2850
(mm)	3360	(mm)	3
/ °	27/20	Hang	1160/1475
	2580/4720	(km/h)	95
LED			
	QL10703hary		
	Isuzu		2
	7.00-16		6
	8/6+5	Front Track (mm)	. 1504
		(mm)	1425
	IV		Isuzu MSB 5
	700p		
		(ML)	(kw)
4jb1cn	Qingling Isuzu (Chongqing) Engine Co., Ltd.	2771	72
LED			
(mm x mm)	3840 x 1760	LED ()	6.8
(m)	1.5		10/8/6
	3840 × 1460	× heigh mm)	1280 × 1440
	3600 × 3000		
LED			
1. LED 2. 3. LED LED P10, P8, P7, P6			

ISUZU 600P P4-P10 LED SMD

[illegible]





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



01

LED SCREEN DISPLAY

High Brightness to ensure crystal clear images in virtually any lighting conditions. Good Heat Dissipation to ensure a long life span, High IP Rating to withstand the most strict weather conditions.



EQUIPMENT CONFIGURATION 02

Equipped with multi-media playing system. High Standard Component with a long life span.

03

ALUMINUM ALLOY CABINET

Light cabinet in aluminum alloy, to reduce the weight of trailer to help it move faster. Also the welding is firm, smooth and even



SAFETY DESIGN 04

power protection, leakage protection, short circuit protection, overload protection and life safety protection grounding measures such as accidentally.

APPLICATION SCENARIOS

