

engine	Isuzu 4HK1-TCG60, power 151KW, air brake, 5-speed gearbox, National VI emission standard		
Wheelbase (mm)	5550mm	Cab	Single row seats, can accommodate
Maximum total mass (kg)	17255	Maximum operating height	45M
Overall dimensions (length x width x height)	9460*2570*3960 (mm)		
Curb Weight (kg)	17060	Rated load of working platform (kg)	400
Work Platform	High Strength Stainless Steel Dimensions : 2000X700X1000(mm)		
Rotating device	360 degree continuous rotation	Maximum operating range	28M
Working range at maximum working	5M	Working height at maximum working range	5M
Outrigger span horizontal/vertical	8200/8900mm	Maximum driving speed	110km/h
Boom type	Seven-section octagonal working arm, synchronously retractable		
Control System	CAN bus control system, equipped with wireless remote control, to achieve stepless speed regulation		
Outriggers	Front V and rear V type, individually adjustable (control)		
operate	Electronically controlled operation, with manual emergency operation		
Leveling system	Hydrostatic automatic leveling	Power take-off system	Mechanical Operation



Whatsapp & Telephone: +86-18607222773 Email:brenda@clclwtruck.com



Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com