

Thiết bị của LPG Bobtail Truck:

1. Đồng hồ đo áp suất
2. Đồng hồ đo nhiệt độ
3. Van bị cắt khẩn cấp
4. Van an toàn
5. Lối lỏng chất lỏng và khí an toàn
6. Bơm LPG

|                            |                                                                                                   |                                        |           |            |
|----------------------------|---------------------------------------------------------------------------------------------------|----------------------------------------|-----------|------------|
| General                    | Overall Dimension                                                                                 | 7000×2300×2600mm                       |           |            |
|                            | Total Mass                                                                                        | 7045Kg                                 |           |            |
|                            | Rated Payload                                                                                     | 2500Kg                                 |           |            |
|                            | Kerb Weight                                                                                       | 4395Kg                                 |           |            |
| Cabin                      | Cab Capacity                                                                                      | 2 persons allowed                      |           |            |
|                            | Air Conditioner                                                                                   | With air conditioner                   |           |            |
| Engine                     | Model/Rated Power                                                                                 | YC4E140-33 / 140HP                     |           |            |
|                            | Type                                                                                              | 4-cylinder inline                      |           |            |
|                            | Displacement                                                                                      | 4256ml                                 |           |            |
|                            | Emission Standard                                                                                 | Euro 3                                 |           |            |
|                            | manufacturer                                                                                      | China Engine                           |           |            |
| Chassis                    | Drive Type                                                                                        | 4X2, Left Hand drive                   |           |            |
|                            | Transmission                                                                                      | 5forwards 1reverser                    |           |            |
|                            | Wheelbase/No. of axle                                                                             | 3800 mm / 2                            |           |            |
|                            | Tyre Specification                                                                                | 7.50R16                                |           |            |
|                            | Tyre Number                                                                                       | 6 <u>tyres</u> and 1 spare <u>tyre</u> |           |            |
|                            | Max Speed                                                                                         | 95 km/h                                |           |            |
|                            | Paint                                                                                             | Metallic paint                         |           |            |
| performance parameter      | Capacity of tank                                                                                  | 5000Liters                             |           |            |
|                            | Inner diameter                                                                                    | 1500mm                                 |           |            |
|                            | <u>Lenght</u> of tank body                                                                        | 3070mm                                 |           |            |
|                            | Tank body net weight                                                                              | 2832kgs                                |           |            |
|                            | Design pressure                                                                                   | 1.77Mpa                                |           |            |
|                            | Design temperature                                                                                | 50℃                                    |           |            |
|                            | Thickness of tank body                                                                            | 10mm                                   |           |            |
| structural style           | Elliptical head, round tank                                                                       |                                        |           |            |
| Inspection test            | proof pressure                                                                                    | 2.30Mpa                                |           |            |
|                            | Air tightness test pressure                                                                       | 1.77Mpa                                |           |            |
|                            | Pressure after gas replacement                                                                    | 0.05-0.1Mpa                            |           |            |
|                            | Non-destructive testing ratio                                                                     | 100%                                   |           |            |
|                            | Oxygen content in tank                                                                            | <3%                                    |           |            |
| Safety accessories         | name                                                                                              | model                                  | specs     | <u>Q/T</u> |
|                            | Floating Ball Level Meter                                                                         | UQZ-25P                                | 1500      | 1          |
|                            | Pressure meter                                                                                    | Y-100T                                 | 0-4Mpa    | 1          |
|                            | Temperature meter                                                                                 | WTQ-280                                | -40℃-60℃  | 1          |
|                            | Safe valve                                                                                        | A412F-25-14                            | DN50/DN25 | 1/1        |
|                            | <u>Emergency</u> cutoff valve                                                                     | QGJ43F-25-7-8                          | DN50/DN25 | 2/2        |
|                            | Shut off valve                                                                                    | J24Q-64                                | DN6       | 2          |
|                            | Ball valve                                                                                        | Q41F-25P-8B/9B                         | DN50/DN25 | 1/1        |
| Other attached components: | LPG Pump<br>25m length hose reel.                                                                 |                                        |           |            |
| Painting                   | One anti corrosion and zinc-rich primer and final painting will be accordance with customer need. |                                        |           |            |

Hình ảnh tham khảo □





Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)







Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)





Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)



المطابقة الزرقاء العالمية



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)



Whatsapp & Telephone: +86-18607222773 Email: [brenda@clclwtruck.com](mailto:brenda@clclwtruck.com)

