

Xe tải phá hủy Shacman 8 × 4 50-60T (360 ° tất cả xoay)

Cabin	Driving type 8x4, right hand driven	
	Two seats, with A/C and one sleeper, 70°hydraulically tillable to the front.	
Vehicle Main Dimensions	Overall dimensions (L x W x H)mm	12000×2500×3600
	Wheel base (mm)	1800+4600+1350
	Wheel track (front/rear) (mm)	2022/1830
Weight in KGS	Tare Weight(KGS)	24000
	Front axles loading capacity(KGS)	2x7500
	Rear axles loading capacity(KGS)	2x16000
Max. driving speed(km/h)	75	
Engine	Brand	CUMMINS
	Model	ISME385-30
	Type	4-stroke direct injection,6-cylinder in-line with water cooling, turbo-charging and inter-cooling
	Horse Power(HP)	385HP
	Emission standard	Euro 2
Gearbox	12JSD180T, 12 speed forward and 2 reverse gear	
Clutch	Reinforced diaphragm clutch, diameter 430mm	
Steering	Integral circulation ball power steering	
Oil tank	400 liters	
Tire	12.00R20 tires, 12 pieces with one spare	
Special Device For Wrecker System		
Hoisting Organ	Rated under-pulling capacity	60000
	Max Under-hoisting Capacity (kg)	30000

	Max Under-hoist length (mm)	3000
	Under hoisting work angle	-10~85°
Lifting Organ	Max lifting capacity(kg)	60000
	Max lifting high(mm)	11680
	Telescope length(mm)	6000
	Winch	30000kgs×2
	Steel rope	50M,Φ30
	Crane luffing angle	5°~ 60°
	Crane rotation angle	360°All Rotation
Landing Leg	Distance between front legs(mm)	7000
	Distance between rear legs(mm)	4000

Hình ảnh tham khảo □





Whatsapp & Telephone: +86-18607222773 Email: brenda@clclwtruck.com



